

# DVE™ Viscometer

our most affordable digital viscometer

## New User Interface

- Keypad control
- Sharp viewing screen for close up or distance viewing

## No calculations required

- Direct reading of viscosity

## Displayed Info:

- Viscosity (cP, P, mPa•s or Pa•s)
- % Torque
- Speed/Spindle

## Easy-to-Use

### Range

push for determining full scale range (FSR) viscosity

### 18 Speeds

for complete range capability

### Bubble level

conveniently located for easy adjustment

**Accuracy: ±1.0% of range**

**Repeatability: ±0.2%**



## What's Included?

Instrument

6 spindles (RV/HA/HB) (p45)

or 4 spindles (LV) (p45)

Spindle Guard Leg\*

Lab Stand (Model A) (p50)

Carrying Case

\*Not applicable to HA or HB torque models

## Optional Accessories

Viscosity Standards (p52)

RV/HA/HB-1 Spindle (p45)

Quick Action Lab Stand (p50)

Temperature Bath (p33-35)

Small Sample Adapter (p38)

UL Adapter (p40)

Thermosel (p36)

DIN Adapter (p44)

Quick Connect/Extension Links (p49)

MODEL	VISCOSITY RANGE cP(mPa•s)		SPEEDS	
	Min.	Max.	RPM	Number of Increments
DVELV	1†	2M	.3-100	18
DVERV	100††	13M	.3-100	18
DVEHA	200††	26M	.3-100	18
DVEHB	800††	104M	.3-100	18

† 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles.

†† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.

M = 1 million cP = Centipoise mPa•s = Millipascal•seconds